D-Link
Building Networks for People

DSL-G604T
Wireless ADSL Router



Home | Advanced | Tools | Status | Help

UPnP

Virtual Server

Lan Clients

SNMP

Filters

Bridge Filters

Routing

DMZ

Parent Control

Firewall

RIP

ADSL

ATM VCC

QoS

Wireless Management

Filters

Filters are used to allow or deny LAN or WAN users from accessing the internet or internal Network.

(•) Outbound Filter ( ) Inbound Filter

IP Outbound Filter

Filters are used to allow or deny LAN users from accessing the internet.

Source IP [ ] ~ [ ] Any IP

Destination IP [ ] ~ [ ] Any IP

Source Port [ ] ~ [ ] Any Port

Destination Port [ ] ~ [ ] Any Port

Protocol TCP,UDP

Action Allow

Apply Cancel Help

ID	Category	Source IP	Destination IP	Prot.	Act.	Enable
1	Outbound	192.168.1.20:2314	Any IP:Any Port	UDP	Allow	☑
2	Outbound	192.168.1.105:3308	Any IP:Any Port	Both	Allow	☑
3	Outbound	192.168.1.105:3306	Any IP:3306	Both	Allow	☐
4	Inbound	Any IP:80	192.168.1.3:80	Both	Allow	☑
5	Inbound	Any IP:9680	192.168.1.3:80	Both	Allow	☑
6	Inbound	Any IP:9622	192.168.1.3:22	Both	Allow	☑